



WD29ATM12

ATM CAMERA, 700TVL, WIDE DYNAMIC, 12 V

KEY FEATURES

- High resolution up to 700 TVL
- Sony 1/3" Sensor
- DNR for low-light image
- HLC(High Light Compensation)
- Automatic defogging function
- 12V power input only



Truly the ultimate ATM camera, Day/Night use with the best possible Wide Dynamic Range image you will find. The ATM camera delivers a clear detailed image in the most challenging lighting conditions.



OPERATIONAL

Imager	SONY@1/3" Super HAD-II Sensor
Horizontal Resolution	700TVL
Active Pixel Count(HXV)	976 x 494 (NTSC)
Lens Type	Fixed Lens
Scanning Frequency	60Hz (NTSC)
Active Pixels	976H x 582V
Min.Scene Illumination	0.3Lux (F1.2, 50IRE, AGC ON)
Iris Control	DC Auto
S/N Ratio	>50dB (100 IRE, F1.2)
Synchronization	Internal or Line Lock, Phase Adjustable
Shutter Speed	AES:1/60'1/100000(NTSC)
Video Output	Composite(75 ohms BNC unbalanced conenctor)

CONTROLS

Sense Up	On/Off
AGC Gain Control	Max. 44.8dB, Gain Selectable
Wide Dynamic Range (WDR)	OFF/ATR-EX/WDR
High-Light Compensation (HLC)	On/Off
Backlight Compensation(BLC)	Full Range, Adjustable
White Balance Control	ATW/Manual/Push/Push Lock/USER1,2/ANTI CR
Auto White Balance Range	Indoor: 1800K~10500K Outdoor:6500K~10500K
Day/Night	Software DAay/Night (AUTO, COLOR, B/W)
Mirror	OFF/M/H/HV
Defog	On(High, Mid,Low)/Off
Motion Detection	ON/OFF (4 Zone Delectable)
Privacy Zone	ON/Off (15 Zone Selectable)
Digital Noise Reduction	3D DNR
E-Zoom	x 255 Max
DIS	Yes
Language	Multi Langauge up to 8 regions

ENVIRONMENTAL

Operation Temperature	-10 degrees C~50 degrees C
Storage Temperature	-20 degrees C~60 degrees C

LENS

Focal length	2.8mm
F-N0	F1.8

ANGLE OF VIEW

Diagonal	128 degrees
Horizontal	98 degrees
Vertical	81.5 degrees

ANGLE OF VIEW

Diagonal	128 degrees
Horizontal	98 degrees
Vertical	81.5 degrees



deView electronics
1420 Lakeside Parkway, Ste. 110, Flower Mound, TX 75028
Phone: (877) 4deView Fax: (214) 222-3339 www.deviewelectronics.com